

Docket No.: P-183



COPY

2683

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Min Soo KIM and Yong Hee LEE

Serial No. 09/766,632

Confirm. No.: 8374

For: DRAWER-TYPE MOBILE PHONE

Technology Center 2600

APR 05 2001

RECEIVED

SUBMISSION OF ORIGINAL SPECIFICATION

Assistant Commissioner for Patents  
Washington, D. C. 20231

Sir:

Submitted herewith is the original Specification. This Specification corresponds to the facsimile copy of the Specification filed on January 23, 2001.

Respectfully submitted,

FLESHNER & KIM, LLP

A handwritten signature in cursive script, appearing to read "Daniel Y.J. Kim".

Daniel Y.J. Kim  
Registration No. 36,186  
Carl R. Wesolowski  
Registration No. 40,372

P. O. Box 221200  
Chantilly, Virginia 20153-1200  
(703) 502-9440 DYK/CRW:tmd  
Date: April 4, 2001

COPY

HA



COPY

## DRAWER-TYPE MOBILE PHONE

### BACKGROUND OF THE INVENTION

RECEIVED  
APR 05 2001  
Technology Center 2600

#### 1. Field of the Invention

The present invention relates to a mobile phone, and more particularly, to a mobile phone having a drawer cover.

#### 2. Description of the Background Art

Generally, as a mobile communication instrument making a communication through a wireless relay of a base station, there are two types of mobile phones: one is a bar type and the other is a folder type.

The bar type mobile phone is typically structured in that a speaker and a microphone are provided in one case, that is, a transmitter and a telephone receiver are integrated, which may be implemented as a flip type by attaching a flip cover for selectively open and close a button part of a main body thereof.

The bar type mobile phone is in the tendency of becoming small for the convenience's sake in carrying, but, in consideration of communication, a distance between the microphone and the speaker should be constantly maintained in the aspect of the structure of the human body. In this respect, the conventional bar type mobile phone has structural shortcomings toward the compact size.

Figure 1 is a schematic perspective view of a folder-type mobile phone in accordance with a conventional art.

As shown in the drawing, in an effort of overcoming the structural restriction of the bar-type mobile phone, a folder-type mobile phone includes a

COPY

speaker (S) provided in an upper case 2, a microphone (M) provided in a lower case 4, and a hinge member (not shown), so that the cases 2 and 4 can be folded and unfolded by virtue of the hinge member at one side.

Accordingly, a user carries the folder-type mobile phone in a state that the upper and the lower cases 2 and 4 are folded, and makes a communication with the other party in a state that the upper and the lower cases 2 and 4 are unfolded, that is, in the state that the microphone (M) and the speaker (S) are opened and closes to the mouth and the ear of the user.

Thus, the folder-type mobile phone is considered an improved type compared to the bar-type mobile phone in the aspect of the convenience for carrying .

However, the conventional folder-type mobile phone disadvantageously causes an inconvenience in that since the microphone and the speaker are separately formed at the upper and the lower cases which are coupled by the hinge member, the user should unfold the upper case by the thumb with one hand holding the lower case or should unfold the upper case by one hand with another hand holding the lower case, for communication.

## SUMMARY OF THE INVENTION

Therefore, an object of the present invention is to provide a drawer-type mobile phone which is capable of providing users' convenience.

Another object of the present invention is to provide a drawer-type mobile phone having a drawer cover slidably movable linearly.

Still another object of the present invention is to provide a drawer-type

mobile phone which is capable of operate a drawer cover by one-touch method.

Yet another object of the present invention is to provide a drawer-type mobile phone in which a speaker is provided on a drawer cover.

Another object of the present invention is to provide a drawer-type mobile  
5 phone having an antenna which is automatically pulled out when a drawer cover is operated.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, there is provided a drawer-type mobile phone including: a main body provided with  
10 a microphone; a drawer cover slidably movable linearly, having a panel form so as for both margins to be moved along both side faces of the main body; a speaker mounted at the upper inner surface of the drawer cover, being connected with an audio amplifier of the main body through a connection member; an antenna movably connected with a tuner terminal of the main body and mounted in a  
15 manner of being able to interwork with (to move along with) the drawer cover; and an operating unit for moving the drawer cover by one touch.

In order to achieve the above objects, the drawer cover has a transparent window at the position corresponding to an LCD part of the main body and is formed in a panel form so that both margins thereof can be movable along the  
20 both side faces of the main body.

In order to achieve the above objects, the operating unit includes a pinion gear mounted at one side of the main body; a rack gear fixedly mounted at one side of the drawer cover to be engaged with the pinion gear; a driving motor mounted at the main body for providing a driving force; a worm gear unit for  
25 transmitting the driving force of the driving motor to the pinion gear; and a control

switch for turning on and turning off the operation of the driving motor.

In order to achieve the above objects, the operating unit includes an automatic moving member for vertically moving the drawer cover; a binding member for selectively binding one end of the drawer cover when the drawer cover is closed and releasing the binding state of the drawer cover when the  
5 drawer cover is opened; and a motion restraining member for restraining the drawer cover from releasing from the main body when the drawer cover is opened.

In order to achieve the above objects, the automatic moving member includes a spring-type pinion gear mounted at one end of the main body and a  
10 rack gear fixedly and horizontally mounted at one side of the drawer cover so as to be engaged with the pinion gear.

In order to achieve the above objects, the binding member includes a hooking protrusion provided at a predetermined portion of the side face inside the drawer cover; a press button having a support bar mounted at side surface of the  
15 main body, extending inwardly of the main body; a fixing support for supporting the front end of the support bar; a hooking piece mounted at the support bar for hooking the hooking protrusion in a closed state; and a twisted spring mounted at the support bar for applying an elastic force to one side of the hooking protrusion.

In order to achieve the above objects, the binding member includes a  
20 metal piece attached at the lower end of the drawer cover; a solenoid attached at a predetermined portion of the main body corresponding to the metal piece; a key circuit board for supplying a voltage to the solenoid; and a press button for turning on or off the key circuit board.

In order to achieve the above objects, the binding member includes a  
25 metal piece attached at the lower end of the drawer cover and a press button

attached to the main body in a manner of being vertically moved, having a magnet piece to attract the metal piece formed at one side thereof.

In order to achieve the above objects, the magnet binding member includes an upper magnet piece attached at the lower end of the drawer cover; and a slide button attached at the main body so as to be horizontally movable by virtue of the spring, having a lower magnet piece to attract the upper magnet piece.

In order to achieve the above objects, the motion refraining member includes a hooking groove formed at the inner side of the drawer cover; and an elastic piece, of which one end is fixed at the main body and the other end is gently bent upwardly, or of which a central portion is gently bent and protruded with both ends fixed at the main body.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

Figure 1 is a schematic perspective view of a folder-type mobile phone in accordance with a conventional art;

Figure 2A and 2B are perspective views of a drawer-type mobile phone in accordance with the present invention;

Figure 3 is a perspective view showing a speaker attached at the inner surface of the drawer cover and a connecting member of the speaker of the drawer-type mobile phone in accordance with the present invention;

Figure 4 is a sectional view of a terminal member which connects a circuit wiring of the speaker to an audio amplifier of a main body of Figure 3 in accordance with the present invention;

Figure 5 shows a structure of attachment of an antenna of the drawer-type mobile phone in accordance with the present invention;

Figure 6 is a sectional view of the antenna attached at the drawer-type mobile phone of Figure 5 in accordance with the present invention;

Figure 7 is a perspective view showing that the antenna is pulled out in a state that the drawer cover of the drawer-type mobile phone is closed in accordance with the present invention;

Figure 8 is a plan view of one embodiment of an operating unit for opening and closing the drawer cover of the drawer-type mobile phone by one touch in accordance with the present invention;

Figure 9 is a sectional view showing a detailed structure of the operating unit of Figure 8 in accordance with the present invention;

Figure 10 is a plan view of another embodiment of the operating unit for moving the drawer cover of the drawer-type mobile phone in accordance with the present invention;

Figure 11 is a sectional view of a spring-type pinion gear of an automatic moving member of Figure 10 in accordance with the present invention;

Figure 12 is a perspective view showing a detailed structure of a mechanical binding member of Figure 10 in accordance with the present invention;

Figure 13 is a schematic view showing a construction of an electromagnetic binding member of Figure 10 in accordance with the present invention;

Figure 14 is a schematic view showing a construction of a single-magnet binding member of Figure 10 in accordance with the present invention;

Figure 15 is a schematic view showing a construction of a double-magnet binding member of Figure 10 in accordance with the present invention; and

Figures 16A and 16B are perspective views showing constructions of a motion refraining member of the drawer-type mobile phone in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

Figure 2A and 2B are perspective views of a drawer-type mobile phone in accordance with the present invention.

As shown in the drawings, the drawer-type mobile phone of the present invention includes a main body 10 having a key pad 12 and an LCD part 13 which are selectively opened and closed, a drawer cover 20 which is slidably moved vertically and an operating unit for controlling the opening and closing operation of the drawer cover 20.

The drawer cover 20 includes a transparent window 201 at a position



corresponding to the LCD part 13 of the main body 10. The both margins of the drawer cover 20 is of a panel form so as to be movable along both side faces of the main body 10. A speaker hole 20a is formed at a predetermined portion of the upper side of the transparent window 201.

5           Figure 3 is a perspective view showing a speaker attached at the inner surface of the drawer cover and a connecting member of the speaker of the drawer-type mobile phone in accordance with the present invention.

          As shown in the drawing, a speaker 2 is provided at the inner upper side of the drawer cover 20, that is, at a position corresponding to the speaker hole 20a.  
10       The speaker 2 is mounted as being supported by a bracket unit 202. A separate cover 22 is attached to the bracket unit 202, so that the speaker 2 can be maintained stably in a fixed state.

          The speaker 2 is connected with the main body 10 through a speaker connecting member. As shown in Figure 3, the speaker connecting member  
15       includes a circuit wiring 30 horizontally attached inside of the drawer cover 20, of which one end is connected with the speaker 2, and a terminal member 40 for connecting the circuit wiring 30 with an audio amplifier (not shown) of the main body 10.

          Figure 4 is a sectional view of a terminal member which connects a circuit  
20       wiring of the speaker to an audio amplifier of a main body of Figure 3 in accordance with the present invention.

          As shown in the drawing, the terminal member 40 includes a plunger terminal 42 of which one end is movably adhered to the surface of the circuit wiring 30 and the other end is connected with the audio amplifier, a terminal case  
25       44 mounted in a manner that the plunger terminal 42 can be linearly moved, and a

compression spring 46 inserted in the case 44 for elastically pressing the plunger terminal 42.

Accordingly, the speaker 2 and the audio amplifier of the main body are maintained to be electrically connected constantly regardless of the opening and closing operation of the drawer cover 20. That is, one end of the plunger terminal 42 is pressed to the circuit wiring 30 due to the elastic force of the compression spring 46 and adhered to the surface of the circuit wiring 30. Thus, even through the plunger terminal 42 is moved along the circuit wiring 30 according to the opening and closing operation of the drawer cover 20, the plunger terminal 42 is maintained to contact the circuit wiring 30, so that the speaker 2 and the audio amplifier of the main body are maintained to be electrically connected constantly.

Figure 5 shows a structure of attachment of an antenna of the drawer-type mobile phone in accordance with the present invention.

As shown in the drawing, the drawer-type mobile phone of the present invention includes an antenna 30 which interworks with the drawer cover 20 when the latter is opened or closed. The antenna 30 includes a head 31 which is protruded upwardly of the drawer cover 20 through the antenna hole 20b and a whip part 32 formed at the lower side of the head 31. A moving terminal 34 connected with the upper and the lower terminals 41 and 42 of the circuit board 43 is attached at the lower end of the whip part 32.

Figure 6 is a sectional view of the antenna attached at the drawer-type mobile phone of Figure 5 in accordance with the present invention.

As shown in the drawing, an antenna binding member includes an outer bushing 50 fixedly mounted at the antenna hole 20b and an inner bushing 52 combined at the inner side of the outer bushing 50, for binding the whip part 32.

The inner bushing 52 is threaded with the outer bushing 50, which are made of a material (i.e., rubber, etc.) having a suitable friction force so that the antenna 30 can be pulled out by a certain external force.

Thus, as shown in Figure 5, when the drawer cover 20 is opened, the  
5 antenna 30 is also pulled out along with the drawer cover 20 to as long as a predetermined height, improving the receiving sensitivity of an electric wave, and the whip part 32 is pulled into the main body 10 as the drawer cover 20 is closed.

When the drawer cover 20 is opened, the antenna 30 is pulled out along with the drawer cover 20, so that the moving terminal 34 is connected with the  
10 upper tuner terminal 41 of the circuit board 43, while, when the drawer cover 20 is closed, the moving terminal 34 is connected with the lower tuner terminal 42 of the circuit board 43. Thus, the antenna 30 is maintained to be electrically connected with the circuit board 43 constantly regardless of the opening and closing of the drawer cover 20.

15 The inner bushing 52 compressively supports the whip part 32 of the antenna 20 to an extent that the former moves the latter. Accordingly, as shown in Figure 7, a user may pull out only the antenna 30 without opening the drawer cover 20 as necessary. When the antenna 30 is pulled out, the moving terminal 34 is hooked at the upper inner side 10-1 of the drawer cover 20, so that the antenna  
20 30 is prevented from releasing from the main body 10.

The opening and closing operation of the drawer-type mobile phone of the present invention will now be described.

Figure 8 is a plan view of one embodiment of an operating unit for opening and closing the drawer cover of the drawer-type mobile phone by one touch in  
25 accordance with the present invention.

As shown in the drawing, the operating unit 100 includes a pinion gear 30 mounted at one side of the main body 10, a rack gear 32 fixedly and horizontally mounted at one side of the drawer cover 20 so as to be in mesh with the pinion gear 30, a drive motor 45 mounted at the main body 10, for providing a driving  
5 force, and a worm gear unit 42 for transmitting the driving force of the drive motor 45 to the pinion gear 30, and a control switch 11 for controlling the operation of the drive motor 45.

Figure 9 is a sectional view showing a detailed structure of the operating unit of Figure 8 in accordance with the present invention.

10 As shown in the drawing, the worm gear unit 42 includes a worm wheel 421 fixedly mounted at the central shaft 301 of the pinion gear 30 and a worm gear 422 mounted at the driving shaft 401 of the drive motor 45 so as to be in mesh with the worm wheel 421.

The control switches 11, as shown in Figure 2A, are formed at the lower  
15 side of the main body 100, having an electrical structure in association with the drive motor 45.

In a state that the drawer cover 20 is closed, when the user operates the control switch 11 and drives the drive motor 45, the rotational force of the drive motor 45 is transmitted through the worm gear 422 and the worm wheel 421 to the  
20 pinion gear 30, so that the pinion gear 30 is rotated.

Thus, according to the rotation of the pinion gear 30, the rack gear 32 in mesh with the pinion gear 30 is moved upwardly, opening the drawer cover 20. At this time, the drive motor 45 is rotated for a predetermined time or for as many as predetermined number of times and then automatically stopped by the  
25 manipulation of the control switch 11, so that the drawer cover 20 can be

prevented from releasing from the main body 10.

Thereafter, when the user terminates using of the mobile phone and closes the drawer cover 20, he or she operates the control switch 11 so that the drive motor 45 is rotated in the opposition direction to the case where the drawer  
5 cover 20 is opened.

Figure 10 is a plan view of another embodiment of the operating unit 200 for moving the drawer cover of the drawer-type mobile phone in accordance with the present invention.

As shown in the drawing, the operating unit 200 includes an automatic  
10 moving member for vertically moving the drawer cover 20 and a binding member for selectively binding one end of the drawer cover 20 in a closed state.

The automatic moving member of the drawer cover 20 includes a spring-type pinion gear 34 (referred to as a pinion gear, hereinafter) mounted at the side of the main body 10 and a rack gear 36 fixedly and vertically mounted at one side  
15 of the drawer cover 20 so as to be in mesh with the pinion gear 34.

Figure 11 is a sectional view of a spring-type pinion gear of an automatic moving member of Figure 10 in accordance with the present invention.

As shown in the drawing, a volute spring 322 is mounted at the pinion gear 34 in a manner that one end thereof is fixed at the central shaft 321 and the  
20 other end is fixed at the outer side of the pinion gear 34. The volute spring 322 holds or release a repulsive force according to the rotation direction of the pinion gear 34.

Thus, in a state that the drawer cover 20 is closed, the volute spring 322 mounted inside the pinion gear 34 is wound, and accordingly, the volute spring  
25 322 has a repulsive rotational force and the drawer cover 20 is maintained to be

firmly fixed by virtue of the binding member.

In this state, when the binding state by the binding member is released, the pinion gear 34 is rotated due to the repulsive elastic force of the volute spring 322, causing the movement of the rack gear 36, so that the drawer cover 20 is  
5 upwardly moved and opened.

Thereafter, after the user terminates using of the mobile phone, he or she pushes the drawer cover 20, the pinion gear 32 in mesh with the rack gear 34 is rotated, according to which the volute spring 322 is wound again, so that the drawer cover 20 is closed and the volute spring 322 has a repulsive rotational  
10 force.

The binding member of the operating unit 200 can be divided into two types according to a structural principle; one is a mechanic binding member using a mechanical binding structure, and the other is a magnetic binding member using a magnetic force.

15 Figure 12 is a perspective view showing a detailed structure of a mechanical binding member of Figure 10 in accordance with the present invention.

With reference to Figures 11 and 12, the mechanic binding member includes a hooking protrusion 38 formed at a predetermined portion of the side face inside the drawer cover 20, a press button 44 having a support bar 441  
20 mounted at the side of the main body 10 and extended inwardly of the main body 10, a fixing support 46 for supporting the front end of the support bar 441, a hooking piece 48 mounted at the support bar 441 for hooking the hooking protrusion 38 in a closed state, and a twisted spring 49 mounted at the support bar 441 for applying an elastic force to one side of the hooking piece 48.

25 The magnetic binding member can be divided into an electromagnetic

type (a solenoid type) and a permanent magnet type.

Figure 13 is a schematic view showing a construction of an electromagnetic binding member of Figure 10 in accordance with the present invention.

5       As shown in the drawing, the electromagnetic binding member includes a metal piece 51 attached at the lower end of the drawer cover 20, a solenoid 52 attached at a predetermined portion of the main body 10 corresponding to the metal piece 51 for generating a magnetic force, a key circuit board 54 for supplying voltage to the solenoid 52 and a press button 56 for turning on or turning  
10   off the key circuit board 54. The key circuit board 54 includes an insulating terminal 55 which interworks with the press button.

The permanent magnet binding member is divided into a single magnet type and a double magnet type.

Figure 14 is a schematic view showing a construction of a single magnet  
15   binding member of Figure 10 in accordance with the present invention.

As shown in the drawing, the single magnet binding member includes a metal piece 60 attached at the lower end of the drawer cover 20 and a press button 56 attached at the main body, being elastically supported so as to be able to be vertically moved by virtue of the spring 62 and having a magnet piece  
20   attracting the metal piece 60 at one side thereof.

Figure 15 is a schematic view showing a construction of a double magnet binding member of Figure 10 in accordance with the present invention; and

As shown in the drawing, the double magnet binding member includes an upper magnet piece 70 attached at the lower end of the drawer cover 20 and a  
25   slide button 76 attached at the main body, being elastically supported so as to be

able to be vertically moved by virtue of the spring 72 and having a lower magnet piece 74 to attract the upper magnet piece 70 at one side thereof. The upper and the lower magnet pieces 70 and 74 have the opposite polarity each other.

The operations of the binding members will now be described.

5

1) mechanic binding member

When the drawer cover 20 is closed, as shown in Figure 12, the hooking protrusion 38 provided at the portion of the side face inside the drawer cover 20 is hooked by the hooking piece 48. At this time, though the hooking protrusion 38 receives a force at one side thereof due to the repulsive rotational force of the volute spring 322 applied to the drawer cover 20, since one end of the hooking piece 48 is hooked by one side of the support 46 and thus not rotated, the hooking protrusion 38 is not moved. Accordingly, the drawer cover 20 is maintained stably in the closed state.

15 When the user depresses the press button 44 to open the drawer cover 20, the hooking piece 48, along with the support bar 441, is moved in the direction that the press button 44 is pressed, so that the hooking piece 48 is released from the hooking protrusion 38.

Accordingly, the restrained state by the hooking piece 48 is released and the drawer cover 20 is opened by virtue of the repulsive rotational force of the volute spring 322 inserted in the pinion gear 32. At this time, the hooking protrusion 38 is moved to the position indicated by dotted line.

Thereafter, when the user terminates using of the mobile phone and closes the drawer cover 20, the hooking protrusion 42 attached at the drawer cover 20 is moved downwardly, pushing the hooking piece 48.

25



Then, the hooking piece 48 is a bit rotated upwardly due to the pushing force by the hooking protrusion 42, making the hooking protrusion 42 to move smoothly. After the hooking protrusion 42 passes, the hooking piece 48 returns to the original position due to the elastic force of the twisted spring 49, restraining the  
5 hooking protrusion 42 from moving.

## 2) magnetic binding member

As shown in Figure 13, in case that the drawer cover 20 is closed, a voltage is supplied from the key circuit board 54 to the solenoid 52. Thus, as an  
10 electro-magnetic force is generated at the solenoid 52, the solenoid 52 and the metal piece 51 are bound, so that the drawer cover 20 is maintained in a closed state.

When the user depresses the press button 56, the insulating terminal 55 is pressed by the press button 56, so that the voltage supplied from the key circuit  
15 board 54 to the solenoid 52 is cut off. Consequently, the electro-magnetic force by the solenoid 52 is removed, and thus, as mentioned above, the drawer cover 20 is opened due to the repulsive rotational force of the volute spring 322 included in the pinion gear 34.

## 20 3) Permanent magnet binding member

As shown in Figure 14, in case where the single magnet binding member is applied, the metal piece 60 attached at the lower end of the drawer cover 20 is attracted to the magnet piece 64 attached at the press button 66 of the main body  
10, thereby maintaining the closed state of the drawer cover 20.

25 Thereafter, when the press button 66 is depressed, the attracted state

between the metal piece 60 and the magnet piece 64 is forcefully separated, resulting in that, as mentioned above, the drawer cover 20 is opened due to the repulsive rotational force of the volute spring 322 included in the pinion gear 32.

Meanwhile, as shown in Figure 15, in case where the double magnet  
5 binding member is applied, the upper magnet piece 70 attached at the lower end of the drawer cover 20 attracts the lower magnet piece 74 attached at the slide button 76 of the main body 10, thereby maintaining the closed state of the drawer cover 20.

At this time, by arranging the magnet pieces 70 and 74 in a manner that  
10 their polarity is the opposite to each other, the closed state of the drawer cover 20 is more stably maintained.

Thereafter, when the slide button 76 is pulled down to move the lower magnet piece 74 for a certain interval, the upper and the lower magnet pieces 70 and 74 are arranged to have the same polarity, causing a repulsive magnetic force.  
15 Thanks to the repulsive magnetic force, the binding state of the drawer cover 20 is released, so that the drawer cover 20 is opened due to the repulsive rotational force of the volute spring 322.

The drawer-type mobile phone of the present invention includes a moving restraining member to prevent the drawer cover 20 from releasing from the main  
20 body 10 when the drawer cover 20 is opened.

Figures 16A and 16B are perspective views showing constructions of a motion refraining member of the drawer-type mobile phone in accordance with the present invention.

As shown in Figures 16A and 16B, the moving restraining member  
25 includes a hooking groove 20b formed at the side of the drawer cover 20 and an

elastic piece 80 provided at one side of the main body 10 contacting the side of the drawer cover 20 to make the drawer cover 20 to move only at one side.

As for the elastic piece 80, as shown in Figure 16A, one end of the elastic piece 80 is fixed at one side of the main body 10 and the other end of the elastic  
5 piece 80 is gently and upwardly bent, or as shown in Figure 16B, the central portion thereof may be gently bent and protruded with the both ends fixed to the main body 10.

Accordingly, when the drawer cover 20 is opened, the hooking groove 20b formed at the side portion of the drawer cover 20 is hooked by the elastic piece 80  
10 provided at the main body 10, so that the drawer cover 20 is not released from the main body 10.

And, when the drawer cover 20 is closed, since the elastic piece 80 is suitably deformed by being pressed under the drawer cover 20, the elastic piece does not interfere the movement of the drawer cover 20.

15 As so far described, the drawer-type mobile phone of the present invention has advantages in that since the drawer cover is attached to the mobile phone, it is very convenient for users to use.

The drawer-type mobile phone of the present invention has a structural characteristic that the distance between the microphone and the speaker is  
20 maintained suitable to the structure of the human body (distance between the mouth and the ear) when the drawer cover is opened, and since the opening and closing operation of the drawer cover is simply manipulated by one touch, it is very convenient to use.

In addition, since the antenna which interworks with the drawer cover is  
25 provided at the inner side of the upper portion of the drawer cover, which is

automatically pulled out along with the drawer cover in case where the mobile phone is used, it is very convenient to use as well as improving the receiving sensitivity.

Moreover, the speaker is mounted at the inner side of the upper portion of  
5 the drawer cover and connected with the audio amplifier of the main body in a simple structure, so that an efficiency can be enhanced in terms of use and production.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be  
10 understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the meets and bounds of the claims, or equivalence of such meets and bounds are therefore intended to  
15 be embraced by the appended claims.

What is claimed is:

1. A drawer-type mobile phone comprising:

a main body having a microphone;

5 a drawer cover mounted at the main body so as to be slidably moved vertically; and

an operating unit for moving the drawer cover by one touch.

2. The mobile phone according to claim 1, wherein the drawer cover

10 includes a transparent window at a portion corresponding to an LCD part of the main body and a speaker hole formed at a predetermined portion of the upper side of the transparent window.

3. The mobile phone according to claim 1, wherein the drawer cover

15 is formed in a panel form so that both margins thereof can be moved along the both side faces of the main body.

4. The mobile phone according to claim 1, wherein a speaker is

mounted at the inner surface of the upper side of the drawer cover.

20

5. The mobile phone according to claim 4, wherein the speaker is

supported by a bracket unit to which a cover is attached.

6. The mobile phone according to claim 4, wherein the speaker is

25 connected with an audio amplifier through a connecting member.

7. The mobile phone according to claim 6, wherein the connecting member comprising:

a circuit wiring attached at the inner side of the drawer cover, of which one end is connected with the speaker; and

5 a terminal member for connecting the circuit wiring with the audio amplifier.

8. The mobile phone according to claim 7, wherein the terminal comprising:

10 a plunger terminal of which one end is movably adhered to the surface of the circuit wiring and the other end is connected with the audio amplifier;

a terminal case mounted so that the plunger terminal can be linearly moved; and

a compression spring inserted in the terminal case, for elastically compressing the plunger terminal.

15

9. The mobile phone according to claim 1, further comprising:

an antenna being movably connected with a tuner terminal which is connected to the main body and interworking with the drawer cover; and

an antenna binding member for binding the antenna.

20

10. The mobile phone according to claim 9, wherein the antenna comprising:

a head protruded upwardly from the drawer cover through the antenna hole;

25

a whip part formed at the lower side of the head; and

a moving terminal formed at the lower side of the whip part and being connected with the tuner terminal of the main body.

11. The mobile phone according to claim 9, wherein the antenna  
5 binding member comprising:  
an outer bushing fixedly mounted at the antenna hole; and  
an inner bushing combined at the inner side of the outer bushing and binding the whip part of the antenna.

10 12. The mobile phone according to claim 11, wherein the inner bushing is threaded with the outer bushing and made of a material having an adequate friction force so that the antenna can be pulled out by an external force.

13. The mobile phone according to claim 12, wherein the material  
15 having an adequate friction force is rubber.

14. The mobile phone according to claim 1, wherein the operating unit comprising:  
a pinion gear mounted at one side of the main body;  
20 a rack gear fixedly mounted at one side of the drawer cover to be engaged with the pinion gear;  
a driving motor mounted at the main body for providing a driving force;  
a worm gear unit for transmitting the driving force of the driving motor to the pinion gear; and  
25 a control switch for turning on and turning off the operation of the driving

motor.

15. The mobile phone according to claim 14, wherein the worm gear unit comprising:

5 a worm wheel fixedly mounted at the central shaft of the pinion gear; and  
a worm gear mounted at the driving shaft of the drive motor, so as to be in mesh with the worm wheel.

16. The mobile phone according to claim 1, wherein the operating unit  
10 comprising:

an automatic moving member for vertically moving the drawer cover;

a binding member for selectively binding one end of the drawer cover when the drawer cover is closed and releasing the binding state of the drawer cover when the drawer cover is opened; and

15 a motion restraining member for restraining the drawer cover from releasing from the main body when the drawer cover is opened.

17. The mobile phone according to claim 16, wherein the automatic moving member comprising:

20 a spring-type pinion gear mounted at one end of the main body; and

a rack gear fixedly and horizontally mounted at one side of the drawer cover so as to be engaged with the pinion gear.

18. The mobile phone according to claim 17, wherein a volute spring  
25 of which one end is fixed at the central shaft and the other end is fixed at the outer



side of the pinion gear, is mounted at the pinion gear, for holding or releasing a repulsive force according to the rotation direction of the pinion gear.

19. The mobile phone according to claim 16, wherein the binding  
5 member comprising:

a hooking protrusion provided at a predetermined portion of the side face  
inside the drawer cover;

a press button having a support bar mounted at side surface of the main  
body, extending inwardly of the main body;

10 a fixing support for supporting the front end of the support bar;

a hooking piece mounted at the support bar for hooking the hooking  
protrusion in a closed state; and

a twisted spring mounted at the support bar for applying an elastic force to  
one side of the hooking protrusion.

15

20. The mobile phone according to claim 16, wherein the binding  
member comprising:

a metal piece attached at the lower end of the drawer cover;

a solenoid attached at a predetermined portion of the main body  
20 corresponding to the metal piece;

a key circuit board for supplying a voltage to the solenoid; and

a press button for turning on or off the key circuit board.

21. The mobile phone according to claim 16, wherein the binding  
25 member comprising:

a metal piece attached at the lower end of the drawer cover; and  
a press button attached to the main body in a manner of being vertically moved, having a magnet piece to attract the metal piece formed at one side thereof.

5

22. The mobile phone according to claim 16, wherein the binding member comprising:

an upper magnet piece attached at the lower end of the drawer cover; and  
a slide button attached at the main body so as to be horizontally movable  
10 by virtue of the spring, having a lower magnet piece to attract the upper magnet piece.

23. The mobile phone according to claim 16, wherein the motion refraining member comprising:

15 a hooking groove formed at the inner side of the drawer cover; and  
an elastic piece formed at one side of the main body so as to be hooked by the hooking groove when the drawer cover is opened.

24. The mobile phone according to claim 23, wherein the elastic piece  
20 is formed in a manner that one end thereof is fixed at the main body and the other end is gently bent upwardly.

25. The mobile phone according to claim 23, wherein the elastic piece is formed in a manner that the central portion thereof is gently bent and protruded  
25 with both ends fixed at the main body.

26. The mobile phone according to claim 23, wherein the elastic piece is made of a material which is suitably deformed as being pressed by the drawer cover when the drawer cover is closed.

5

27. A drawer-type mobile phone comprising:

a main body provided with a microphone;

a drawer cover slidably movable linearly, having a panel form so as for both margins thereof to be moved along both side faces of the main body;

10 a speaker mounted at the upper inner surface of the drawer cover, being connected with an audio amplifier of the main body through a connection member, and

an operating unit for moving the drawer cover by one touch.

15

28. A drawer-type mobile phone comprising:

a main body provided with a microphone;

a drawer cover slidably movable linearly, having a panel form so as for both margins thereof to be moved along both side faces of the main body;

20 a speaker mounted at the upper inner surface of the drawer cover, being connected with an audio amplifier of the main body through a connection member,

an antenna movably connected with a tuner terminal of the main body and mounted in a manner of being able to interwork with the drawer cover; and

an operating unit for moving the drawer cover by one touch.

25

29. A drawer-type mobile phone comprising:  
a main body provided with a microphone;  
a drawer cover slidably movable linearly, having a panel form so as for  
5 both margins to be moved along both side faces of the main body;  
an automatic moving member for vertically moving the drawer cover;  
a binding member for selectively binding one end of the drawer cover  
when the drawer cover is closed and releasing the binding state of the drawer  
cover when the drawer cover is opened; and  
10 a motion restraining member for restraining the drawer cover from  
releasing from the main body when the drawer cover is opened.



## ABSTRACT OF THE DISCLOSURE

A drawer-type mobile phone includes a main body provided with a microphone; a drawer cover slidably movable linearly, having a panel form so as for both margins to be moved along both side faces of the main body; a speaker mounted at the upper inner surface of the drawer cover, being connected with an audio amplifier of the main body through a connection member; an antenna movably connected with a tuner terminal of the main body and mounted in a manner of being able to interwork with the drawer cover; and an operating unit for moving the drawer cover by one touch. The drawer cover has a transparent window at the position corresponding to an LCD part of the main body and is formed in a panel form so that both margins thereof can be movable along the both side faces of the main body.

15

COPY